



# Technical Data Sheet

## Municipal Application Guide

*Utilizing the Direct Pour Method*

### Treatment:

One 40 lb Box will treat 300' ft. of 8-10" pipe.

### Tools/Equipment:

- 1 – 40 lb box of RootX®
- 25-30 Gallons of water



# 1

### Prepare for the RootX® application

To start the application, assemble the equipment needed; you will need 1- 40 lb. box of RootX® and 25 -30 gallons of water. Release the thumb ties on the two – 20 lb. bags of RootX®. Shake both bags back and forth for at least a minute to mix thoroughly.



# 2

### Apply the RootX® directly into the manhole

After the RootX® is thoroughly mixed cut the top of the bags off. Then pour the RootX® into the manhole directing it toward the outgoing invert or downstream side. Try to direct your pour into the trough as opposed to on the bench. You want the product to flow down the line and foam up, and not just foam up inside the manhole.



# 3

### Add the water

Add 25-30 gallons of water to activate the RootX® and to get it to flow down the line. Even though the RootX® may be gone from the manhole continue to add the remaining water to carry the foam down the line. You are now ready to move onto the next RootX® application.

For more information or to order, visit us on the web at [www.rootx.com](http://www.rootx.com), email us at [rootx@rootx.com](mailto:rootx@rootx.com), or give us a call at 1-800-844-4974.