



Technical Data Sheet

2 & 4lb. RootX® Square Jars with Funnel

Treatment:

- 2 lb. jar will treat approximately 50ft. of 4-inch pipe
- 4 lb. jar will treat approximately 100ft. of 4-inch pipe, or 75ft. of 6-inch pipe

Tools/Equipment:

Chemical-resistant gloves, chemical-resistant apron, 5-gallon bucket and clean water

Preparing the RootX® Funnel Jar for use:

1

Unscrew lid from top of container



2

Attach the funnel

Attach the mixing funnel/applicator by threading onto the opening where the lid was in the square container.



3

Mix RootX® components


Grasping the bottom of the square container and the narrow end of the mixing funnel applicator (putting a hand over the mixing funnel/applicator cap located at the narrow end of the mixing funnel/applicator), rock the square container with the mixing funnel/applicator attached, back and forth for approximately one minute, allowing the two dry components of RootX® to go into the funnel and then back into the square container several times.



4

Apply RootX®

After the one minute mixing process, you may remove the cap from the narrow end of the mixing funnel/applicator and pour the entire contents of the dry product mixture through the funnel/applicator directly into a sewer cleanout or toilet bowl if a sewer cleanout is not available.



See reverse side for specific toilet or sewer cleanout application procedures



Technical Data Sheet (continued)

2 & 4 lb. RootX® Square Jars with Funnel

Sewer Cleanout Application:


5

Pour entire contents of RootX® Funnel Jar into cleanout.




6

Flush toilet two times (or up to six times for a 1.6 gallon low flow toilet).



(or)


Add 5-10 gallons of water into the cleanout to push the foam down throughout the sewer line.



Toilet Application:

5

Flush the toilet and add the dry mixture* into the toilet bowl as the water is going down the drain.



**to avoid foam overflow, use no more than 2 lbs. of RootX in a toilet bowl.*

6

If foam comes back up into the toilet bowl, flush toilet with 5 gallons of water to push foam down the toilet drain.



7

Restrict water usage from 4–6 hours after application

For Precautionary Statements and more specific information, please refer to the RootX® label.



THE RIGHT SOLUTION. RIGHT NOW.

EPA Reg. No. 68464-1