



The Root Intrusion Solution

RootX Conversion Table

Direct Pour Applications (These numbers are dependent upon water flow capacity.)

<u>Pipe Size</u>	<u>Pipe Length</u>	<u>Amount of RootX Required</u>
8"	300'	40 lbs
10"	200'	40 lbs
12"	150'	40 lbs

FDU 300 Applications (Standard Pipe Diameters 8 – 18")

<u>Pipe Size</u>	<u>Pipe Length</u>	<u>Amount of RootX Required</u>	<u>Retrieval Rate</u>
8" – 18"	250'	20 lbs	25 ft/min = 2.4 sec/ft
8" – 18"	300'	20 lbs	30 ft/min = 2 sec/ft
8" – 18"	350'	20 lbs	35 ft/min = 1.7 sec/ft
8" – 18"	400'	20 lbs	40 ft/min = 1.5 sec/ft

FDU 300 Applications (Large Pipe Diameters 20 – 48")

<u>Pipe Size</u>	<u>Pipe Length</u>	<u>Amount of RootX Required</u>	<u>Retrieval Rate</u>
20"*	300'	20 lbs	30 ft/min = 2 sec/ft
20"*	400'	20 lbs	40 ft/min = 1.5 sec/ft
24"*	350'	20 lbs	35 ft/min = 1.7 sec/ft
30"*	300'	20 lbs	30 ft/min = 2 sec/ft
36"*	200'	20 lbs	20 ft/min = 3 sec/ft
48"*	100'	20 lbs	10 ft/min = 6 sec/ft

* For large pipe diameters (20" and larger) the FDU 300 Applicator nozzle must be placed on a skid to center it within the pipe.