



Technical Data Sheet

Grease-X Emulsifier Applications for Lift Stations

Tools/Equipment:

- Grease-X Emulsifier 5 Gallon Pail
- Water source to mix with Emulsifier and to rinse the lift station
- Pump sprayer for surface applications



Lift Station Surface Applications

- 1** Gather tools required for lift station application
You will need Grease-X Emulsifier, a pump sprayer, and a water source for rinsing the lift station and adding any needed water to the pump sprayer.



2

Locate and expose grease covered area

Pump out the lift station far enough to expose the F.O.G. (fats, oils, and grease) covered areas. Using water, spray the surface to remove any loose surface F.O.G.


3



Fill pump sprayer

For light to medium F.O.G., mix in a pump sprayer at a ratio of 50/50 water to Emulsifier making sure to add the water first then add the Emulsifier. For heavy F.O.G., use Grease-X Emulsifier at full concentration.

4



Apply the Emulsifier

Spray a generous coating of Emulsifier on all surfaces with F.O.G. Wait 15 minutes to allow Emulsifier to penetrate thoroughly.

5



Rinse with high pressure

Rinse with high pressure water all coated areas with a hose nozzle, jet truck or pressure washer.

To order Grease-X® Emulsifier, visit our website at www.RootX.com, or call 1-800-844-4974