



Technical Data Sheet

2 & 4 lb. RootX® Square Jars with Funnel

Treatment:

- **2 lb. jar will treat approximately 50ft. of 4-inch pipe**
- **4 lb. jar will treat approximately 100ft. of 4-inch pipe, or 75ft. of 6-inch pipe**

Tools/Equipment:

- **Chemical-resistant gloves**
- **Chemical-resistant apron**
- **5 gallons of water per pound of RootX® used**

Preparing the RootX® Funnel Jar for use:

1

Unscrew lid from top of container



2

Attach the funnel

Attach the mixing funnel/applicator by threading onto the opening where the lid was in the square container.



3



Mix RootX® components

Grasping the bottom of the square container and the narrow end of the mixing funnel applicator (putting a hand over the mixing funnel/applicator cap located at the narrow end of the mixing funnel/applicator), rock the square container with the mixing funnel/applicator attached, back and forth for approximately one minute, allowing the two dry components of RootX® to go into the funnel and then back into the square container several times.

See reverse side for specific toilet or sewer cleanout application procedures



Technical Data Sheet (continued)

2 & 4 lb. RootX® Square Jars with Funnel

Sewer Cleanout Application:

4

Pour entire contents of RootX® Funnel Jar into cleanout.



5

Add 5 gallons of water per pound of product used into the cleanout to push the foam down throughout the sewer line.



Toilet Application:

4

Flush the toilet and add the dry mixture* into the toilet bowl as the water is going down the drain.



* to avoid foam overflow, use no more than 2 lbs. of RootX in a toilet bowl.

5

Immediately add 10 gallons of water into toilet (2 five gallon buckets consecutively).



6

Restrict water usage from 4–6 hours after application



THE RIGHT SOLUTION. RIGHT NOW.



For more information or to order, visit us on the web at www.rootx.com, email us at rootx@rootx.com, or give us a call at 1-800-844-4974.